

SOLARSKIN

An aesthetic overlay that allows a solar panel to display any static color, pattern, or design

30+ YEAR DURABLE FILM

easily applied like a graphics vinyl

CUT TO SIZE

for any brand of solar module

PROJECT YIELD

up to 99%

TESTED AT NREL

the nation's leading solar lab

COLOR RETENTION

long term, with no yellowing or bubbling

PROTECTS MODULE

against chemical and UV degradation

SELF-CLEANING

anti-graffiti surface finish

ANTI-GLARE

cuts down glare from traditional modules

REMOVABLE

without damaging underlying panel

TAX CREDIT APPLICABLE

qualifies for federal ITC and local incentives

10 YEAR WARRANTY



SOLARSKIN Fully tested and commercially available





Florida and Arizona Outdoor Testing Continuous exposure in harshest climate conditions

Installations for paying customers AZ, CA, CO, DC, FL, IL, IN, MA, MI, MN, NJ, NY, SC, SD, TX, VA, VT, WI

Temperature Cycling 200 cycles of -40C to +85C (per IEC 61215)

Humidity Freeze 10 cycles of -40C to +85C, @85% humidity (per IEC 61215)

Damp-Heat 1,000 hrs of 85C + 85% humidity (per IEC 61215)

UV Exposure 3,000 hrs of 2-sun intensity

- Light Transmission
- Flash Testing
- Anti-delamination
- Anti-yellowing
- Anti-browning
- ✓ Long-term Colorfastness
- ASTM D714-02 (Blistering)
- ASTM D660-93 (Checking)
- ASTM D661-93 (Cracking)
- ASTM D3274-09 (Dirt Retention)



TESTED AT





